JET LIGHTING®

Project:

Fixture Type:

Location:

Contact/Phone:

DESCRIPTION

Feature

- Optical grade PC cover, good light transmission, anti-aging, and difficult to damage.
- Aluminum alloy shell with high-thermal conductivity good heat dissipation, vacuum clean spray, corrosion resistance, and no paint stripping.
- Three-dimensional rotation, large rotation angle, adjust conveniently
- \bullet Light emitting protection design, not affected by weather.
- \bullet Sensor angle is adjustable, long sensing distance, and high sensitivity

Listings

- ETL Listed
- DLC Qualified



JT2-SECURITY

LED Security Light









PERFORMANCE DATA

Model No.	Voltage	ССТ	Wattage	Lumen	Finish	Dimensions	Beam Angle	Frequency	CRI
JT2-SECURITY-BR-3K	120V	3000 K	20W	1900	White	14.6" x 7.9" x 6"	100°	50/60 Hz	>80
JT2-SECURITY-WH-3K	120V	5000 K	20W	1900	Bronze	14.6" x 7.9" x 6"	100°	50/60 Hz	>80
JT2-SECURITY-BR-5K	120V	3000 K	20W	1900	White	14.6" x 7.9" x 6"	100°	50/60 Hz	>80
JT2-SECURITY-WH-5K	120V	5000 K	20W	1900	Bronze	14.6" x 7.9" x 6"	100°	50/60 Hz	>80